



# Bearing Mounting Fits

## Shaft Seat Diameter Ball Bearings 6200 - 6300

6200 - 6300	0.3939/ 0.3936
6201 - 6301	0.4726/ 0.4723
6202 - 6302	0.5908/ 0.5905
6203 - 6303	0.6695/ 0.6692
6204 - 6304	0.7878/ 0.7875
6205 - 6305	0.9847/ 0.9844
6206 - 6306	1.1815/ 1.1812
6207 - 6307	1.3785/ 1.3780
6208 - 6308	1.5753/ 1.5749
6209 - 6309	1.7722/ 1.7718
6210 - 6310	1.9690/ 1.9686
6211 - 6311	2.1660/ 2.1655
6212 - 6312	2.3628/ 2.3623
6213 - 6313	2.5597/ 2.5592
6214 - 6314	2.7565/ 2.7560
6215 - 6315	2.9534/ 2.9529
6216 - 6316	3.1502/ 3.1497
6217 - 6317	3.3472/ 3.3466
6218 - 6318	3.5440/ 3.5434
6219 - 6319	3.7409/ 3.7403
6220 - 6320	3.9377/ 3.9371
6221 - 6321	4.1350/ 4.1344
6222 - 6322	4.3318/ 4.3312
6224 - 6324	4.7255/ 4.7249
6226 - 6326	5.1194/ 5.1187
6228 - 6328	5.5131/ 5.5124
6230 - 6330	5.9071/ 5.9061

## Housing Seat Diameter For both Ball and Roller Bearings

200	1.1816/ 1.1811	300	1.3786/ 1.3780
201	1.2604/ 1.2598	301	1.4573/ 1.4567
202	1.3786/ 1.3780	302	1.6541/ 1.6535
203	1.5754/ 1.5748	303	1.8510/ 1.8504
204	1.8510/ 1.8504	304	2.0479/ 2.0472
205	2.0479/ 2.0472	305	2.4416/ 2.4409
206	2.4416/ 2.4409	306	2.8353/ 2.8346
207	2.8353/ 2.8346	307	3.1503/ 3.1496
208	3.1503/ 3.1496	308	3.5442/ 3.5433
209	3.3474/ 3.3465	309	3.9379/ 3.9370
210	3.5442/ 3.5433	310	4.3316/ 4.3307
211	3.9379/ 3.9370	311	4.7253/ 4.7244
212	4.3316/ 4.3307	312	5.1191/ 5.1181
213	4.7253/ 4.7244	313	5.5128/ 5.5118
214	4.9223/ 4.9213	314	5.9065/ 5.9055
215	5.1191/ 5.1181	315	6.3002/ 6.2992
216	5.5128/ 5.5118	316	6.6939/ 6.6929
217	5.9065/ 5.9055	317	7.0876/ 7.0866
218	6.3002/ 6.2992	318	7.4814/ 7.4803
219	6.6939/ 6.6929	319	7.8751/ 7.8740
220	7.0876/ 7.0866	320	8.4657/ 8.4646
221	7.4814/ 7.4803	321	8.8594/ 8.8583
222	7.8751/ 7.8740	322	9.4499/ 9.4488
224	8.4657/ 8.4646	324	10.2375/ 10.2360
226	9.0562/ 9.0551	326	11.0249/ 11.0236
228	9.8436/ 9.8424	328	11.8123/ 11.8110
230	10.6312/ 10.6299	330	12.5998/ 12.5984

## Shaft Seat Diameter Cylindrical Roller Bearings N, NU, NUP & NJ

202 - 302	0.5911/ 0.5906
203 - 303	0.6698/ 0.6693
204 - 304	0.7880/ 0.7875
205 - 305	0.9849/ 0.9844
206 - 306	1.1817/ 1.1812
207 - 307	1.3788/ 1.3784
208 - 308	1.5756/ 1.5752
209 - 309	1.7725/ 1.7721
210 - 310	1.9693/ 1.9689
211 - 311	2.1667/ 2.1662
212 - 312	2.3635/ 2.3630
213 - 313	2.5604/ 2.5599
214 - 314	2.7574/ 2.7567
215 - 315	2.9546/ 2.9536
216 - 316	3.1511/ 3.1504
217 - 317	3.3483/ 3.3474
218 - 318	3.5451/ 3.5442
219 - 319	3.7420/ 3.7411
220 - 320	3.9388/ 3.9379
221 - 321	4.1262/ 4.1354
222 - 322	4.3330/ 4.3322
224 - 324	4.7267/ 4.7259
226 - 326	5.1208/ 5.1198
228 - 328	5.5145/ 5.5135
230 - 330	5.9082/ 5.9072

Diameters shown are based on normal loads, operating temperatures and current industry fitting practices.

- Applies to standard ABEC 1 only -



Philadelphia, PA  
800-523-3382

Gastonia, NC  
888-456-6233

Hebron, KY  
866-598-5773

Pelham, AL  
866-987-1915

Tampa, FL  
866-839-4848

Grain Valley, MO  
888-691-1927

